



# FORCE/2 HP

Intec Part # K20022 w/wired remote; K20023 w/wireless remote *Insulation Blowing Machine*

## Professional Grade – High Performance to meet Contractors’ Demands



**Easy to find power: 2-15amp 115V circuits**  
1 for blower, 1 for agitator

**High pressure provides fast & efficient dense pack**  
Powerful 2-stage blower & one-way valve provides many capabilities with high volume, high pressure, and long-life

**Twist-Lock electrical receptacles**  
Hold cord in place  
Use with Intec’s heavy duty 12/3 power cords or your own

- High Production\***
- 96 bags/hr cellulose; 2400 lbs/hr.
  - 23 bags/hr fiberglass; 700 lbs/hr.
  - 70 bags/hr rock wool; 2100 lbs/hr.

*\*testing per ASTM C519 standards.*

*System shown with standard heavy duty wired remote & industry exclusive urethane jacketed controls for enhanced durability*

Intec’s **FORCE/2 HP** comes with these industry leading components on which it has built its reputation for durability and reliability:

- ✓ **Polyethylene construction:** rust-free, lightweight, and extremely durable.
- ✓ **Intec’s urethane seals:** last 2-3X longer than industry standard providing higher pressures & increased production rates over longer periods of time with less maintenance.
- ✓ **Stainless steel airlock plates:** provide long wear life vs. industry standard airlock construction.
- ✓ **Direct-drive transmission:** fewer moving parts provides longevity with little maintenance.

*integrity*

*excellence*

*innovation*

*trust*

800-666-1611

[www.inteccorp.com](http://www.inteccorp.com)

Click pictures for website link

Rev: 20180124




**Intec’s Professional Grade Equipment**  
Engineered for High Productivity Built-to-Last For High Value Generation

**FORCE®**

Insulation Blowing Machines



**Specifications**



- Weight: 283lbs (128kg)
- Transmission: Durable direct drive – no chains
- Hose outlet: 3 inches (7.6cm)
- Electrical: 115VAC – 2 -15amp circuits required
- Blower: 115 VAC – 15 amp input, two-stage with one way valve
- Agitator motor: 1-½ HP 115VAC-15amp input
- Hopper: 9 cubic feet (13 with hopper extension)
- Warranty: 1 year, limited

*Specifications subject to change; contact Intec for current specifications*

**Accessories**



Kits for Dense Pack, Blow Behind Netting, and Spray-on



Hopper Extension



Wheel Kit



Swivel hose connectors & hose kits



*Backed by Intec's industry leading Technical Service. Training & Accessories are available to increase your efficiencies.*

**Machine Features**

- ✓ Wired Remote standard with *Intec Exclusive* impact resistant Urethane head.
- ✓ Long lasting Blower: Infinity brush technology with one-way valve to prevent insulation from coming into contact with blower combine to provide exceptionally long life.
- ✓ Industrial Grade Wireless transmitter (optional) comes with four placement options.




Jacket for Wrist or Hose      Lanyard      Belt Clip


- ✓ Polyethylene construction: rust-free, lightweight, and extremely durable – will not dent.
- ✓ Urethane seals: last 2-3X longer than belted rubber providing higher pressures & production rates over time with less maintenance.



- ✓ Stainless steel airlock plates: provide long wear life vs. industry standard airlock construction.
- ✓ Direct-drive transmission: fewer moving parts provides longevity with little maintenance.



Distributed by



**Manufactured by**

Insulation Technology Corporation, d.b.a. Intec  
4040 Kodiak Court  
Frederick, CO 80504

Click pictures for website link



**1-800-666-1611**  
**www.inteccorp.com**

Local: 303-833-6644  
Fax: 303-833-6650  
sales@inteccorp.com



... it's the 'tec' inside that counts!