

## Redesigned for enhanced value | HP2 = 2 blowers for more power

### Durable & Dependable

Direct drive transmission, automatic chain tensioner, and industry exclusive long lasting urethane airlock seals enhance the system's reliability to deliver years of trouble-free service.

### Ease of Use

Built in handle & wheels, and nimble weight balance provide ultimate portability into your truck, trailer, and jobsite -- including thru standard door openings. Simple to operate control panel and wired remote provide for ease of operation from either the unit or remotely.

### Versatile

Install cellulose, fiberglass, or stonewool in attics, damp spray, dense pack, drill & fill, and net & blow applications.

### High Production Rates

20 minute install of R-19 cellulose, fiberglass or stonewool in a 1000 square foot attic is made possible by its high production rates.



<u>Production</u>	lbs/min
Cellulose	28 – 37
Fiberglass	11 - 15

Note: FORCE/3 HP testing per ASTM C519 standards.

Intec's **FORCE/3 HP2** comes with these industry leading components on which it has built its reputation for durability and reliability:

- ✓ **Urethane seals:** last 2-3X longer than belted rubber providing higher pressures & increased production rates over longer periods of time with less maintenance.
- ✓ **Stainless steel airlock plates:** provide long wear life vs. industry standard airlock construction.
- ✓ **Direct-drive transmission:** fewer moving parts provides longevity with little maintenance.

integrity

excellence

innovation

trust

303-833-6644

[www.inteccorp.com](http://www.inteccorp.com)

Rev: 20240120



# FORCE<sup>®</sup>

Insulation Blowing Machines



MEGA Beast

Cyclone

Fiber Force

FORCE/2 HP

FORCE/3 HP2

TURBO FORCE

FORCE 5250

FORCE 5650











FORCE 5850

**Specifications**



- Weight: HP2 = 350lbs (159kg)
- Transmission: Durable worm gear direct drive
- Hose outlet: 3 inches (7.6cm)
- Electrical: 115VAC (230VAC optional)  
3 - 15amp circuits with FORCE/3 HP2
- Blowers: 115 VAC – 15 amp, 2-stage generate high pressure and airflow.
- Agitator motor: 115VAC-15amp input
- Hopper: 11-½ cubic feet
  - 1 bag cellulose; ½ bag fiberglass
- Warranty: 1 year, limited

**Machine Features**

- ✓ 100' Wired Remote with heavy duty cord standard with *Intec Exclusive* impact resistant Urethane head. 150' optional. 
- ✓ GOWIRELESS – optional Long Range Transmission High Performance wireless with four placement options
  -  Jacket for Wrist or Hose
  -  Lanyard
  -  Belt Clip
  -  Belt Clip
- ✓ Variable Speed High Powered Blower 
- ✓ Quick setting gate 
- ✓ Urethane airlock seals last 2-3X longer than belted rubber -- providing higher pressures & production rates over time with less maintenance. 
- ✓ Quick clean blower filter 
- ✓ Stainless steel airlock plates provide long wear life vs. industry standard airlock construction. 
- ✓ Large Hopper
- ✓ Direct-drive transmission: fewer moving parts provides longevity with little maintenance.

**Backed by Intec's industry leading Technical Service.**  
**Training & Accessories are available to increase your efficiencies.**

**Professional Grade – Heavy Duty Capabilities**



Dense Pack



Blow Behind Netting



Spray On



Attics

Maximize your **Return On Investment**



With Intec blowing machines

Distributed by



**Manufactured by**

Insulation Technology Corporation, d.b.a. Intec  
9251 Bruin Boulevard  
Frederick, CO 80504

Click pictures for website link 



Local: 303-833-6644  
Fax: 303-833-6650  
sales@inteccorp.com

[www.inteccorp.com](http://www.inteccorp.com)

... it's the 'tec' inside that counts!

