

FORCE® Insulation Blowing Machines

High Capabilities & Low Maintenance

Gas or Electric Powered



FORCE 5850

part #: FORCE 5850 GW



FORCE 5650

part #: FORCE 5650 GW



FORCE 5250

part #: FORCE 5250 GW



Focus Applications:
 ✓ Attics
 ✓ Walls

All come with:

- High Build Quality for Total Reliability
- Oversized components for Long Life
- Easy Access Airlock Seals simplify maintenance
- Advanced Material Feed
- Large Hinged Loading Platform
- Fresh Air Inlets standard
- Control panel or remote operation
- 150' wired remote w/ long-lasting controls
- LRT/HP industrial wireless controls (optional)

FORCE/2 HP

part#: K20023 HP GW



- ✓ Polyethylene construction: rust-free, light weight, & durable
- ✓ Direct-drive transmission: minimal maintenance
- ✓ High Production

integrity

FORCE/3 HP2

part # K30000 HP2 GW



- ✓ Direct-drive transmission provides low maintenance
- ✓ High Production

excellence

TURBO FORCE HP2 & HP MAX

part#: 40003 GW for HP2
40031 GW for HP MAX

- ✓ Revolutionary tilt back design simplifies access to airlock, agitators, and all working components
- ✓ High Production



innovation

trust



FORCE® Insulation Blowing Machines



MEGA Beast Cyclone Fiber Force FORCE/2 HP FORCE/3 HP2 TURBO FORCE FORCE 5250 FORCE 5650 FORCE 5850

303-833-6644

Rev: 20240620

www.inteccorp.com

FORCE® Insulation Blowing Machines

	cellulose										fiberglass										
	Portability	Weight (lbs)	Electrical Requirements 120V (240V available)	Hopper size (cu ft)	Install Time (minutes) R19, 100sq ft attic	Production (bs/m)	Dense Pack Retrofit Recommended	Hopper Capacity (#bags)	Install Time (minutes) R19, 100sq ft attic	Production (bs/m)	Dense Pack Retrofit Recommended	Hopper Capacity (#bags)	Portability	Weight (lbs)	Electrical Requirements 120V (240V available)	Hopper size (cu ft)	Install Time (minutes) R19, 100sq ft attic	Production (bs/m)	Dense Pack Retrofit Recommended	Hopper Capacity (#bags)	
	142 194	1-15amp	5.3 / 9	42	12 - 16	720 - 970	yes	1/2	64	3 - 4	180 - 255	yes	1/3								
	150	1-15amp	5.3 / 9	39	13 - 17	780 - 1020	no	1-2	38	5 - 7	300 - 400	yes	1/2								
FORCE/2 HP	283	2-15amp	9 / 13	16	30 - 40	1860 - 2400	yes	1-2	20	9 - 11	540 - 660	yes	1/2								
FORCE/3 HP2	350	2-15amp	11.5	18	28 - 37	1740 - 2270	yes	1	17	11 - 14	660 - 840	yes	1/2								
	478	3-15amp	15	15	31 - 41	1920 - 2460	yes	2-3	17	12 - 15	720 - 900	yes	1/2 - 1								
	488	2-15amp 1-20amp	15	12	41 - 55	2520 - 3200	yes	2-3	12	15 - 20	900 - 1200	yes	1/2 - 1								
	1015	gas	45	15	33 - 42	2000 - 2500	yes	5-7	17	12 - 16	720 - 1000	yes	2 - 3								
	1500	gas	49	8	73 - 84	4440 - 5000	No	8-10	8	25 - 35	1500 - 2000	No	3 - 4								
	1750	gas	68	7	75 - 95	4500 - 5500	yes	11 - 12*	7	30 - 39	1800 - 2,200	yes	4 - 5*								

Rental, Retail & Lumberyard Contractor

- Notes:
1. Department of Energy requires outlet pressure >=2.9psi (i.e. 80 inches of water) for cellulose dense pack to achieve 3.5lbs/cu-ft density; psi measured at sea level.
 2. Dense Pack capability provides installers with additional market opportunities and resulting profit.
 3. Intec testing according to ASTM. Hose length, diameter, manufacturer brand, lift height, and humidity impact production rates.

Distributed by



... it's the 'tec' inside that counts!

Manufactured by

Insulation Technology Corporation, d.b.a. Intec
 9251 Bruin Boulevard
 Frederick, CO 80504

www.inteccorp.com

Phone: 303-833-6644
 sales@inteccorp.com

