

GENERATOR

Intec Part #:

77001-02


50kW three phase 120/208V

Generator

Professional Grade – 50,000 Watts Meets SPF Contractors' Demands
Tier IV compliant



**Powered by
Fiat PowerTrain
Technologies
Diesel
3.4L turbo**



integrity

excellence

innovation

trust

800-666-1611

www.inteccorp.com

Rev: 20240620



FORCE[®]
Insulation Blowing Machines




Specifications

Information	Unit	Metrics	
Frequency	Hz	60	
Rated Voltage	V	120 / 240	277 / 480
Standby (Apparent Power)	kVA	50.9	
Standby (Reactive Power)	kW	50.9	40.7
Prime (Apparent Power)	kVA	45	
Prime (Reactive Power)	kW	45	36
Maximum	A	211.9	61.2
Continuous	A	187.5	54.1
Breaker	A	225	70
Oil Capacity	qts	8.45	
Voltage Regulation	Typ/%	AVR +/- 1%	
Fuel Consumption	100% Load	4.18 gal/hr	
	75% Load	3.13 gal/hr	
	50% Load	2.09 gal/hr	
	25% Load	1.04 gal/hr	
Dimensions L X W X H	inches	74 X 38 X 49.8	
Dry Weight	lbs	2375	
Net Weight	lbs	2425	

Specifications subject to change; contact Intec for current specifications

Dimensions



Features


GENERATOR

- Low vibration and smooth running
- Quiet and clean running engines
- Mains breaker included
- Monitoring of Voltage, Frequency, and Current
- Fuel efficient operation with electronic fuel systems
- Safety shutdown for temperatures, pressure, & emergency stop
- Mecc-Alte Generator
- Deep Sea Controls

POWER CONFIGURATIONS

- Single phase & Three phase available

Distributed by



Manufactured by

Insulation Technology Corporation, d.b.a. Intec
9251 Bruin Boulevard
Frederick, CO 80504



phone: 303-833-6644

www.inteccorp.com

sales@inteccorp.com



... it's the 'tec' inside that counts!