

Intec Part #'s:

- FORCE 5250 – wired remote
- FORCE 5250 GW – GOWIRELESS remote

Packages available


Truck Mount Insulation Blowing Machine


**FORCE® - The Truck Mount Blowing Machine Brand that will change the industry standard**


❖ **Engineered for High Productivity**

❖ **Built-to-Last for High Value Generation**



 **High return on investment –**  
*High Build Quality provides Reliable & Dependable operation...so you can focus on making \$\$\$.*

 **Application Versatility –**  
*Attics, BIBs, Dense Pack, Spray-on; Cellulose, Fiberglass, and Stone Wool.*

 **Consistent Performance**  
*With Intec Quick-Access™ features, machine adjustments & maintenance are simplified to effortlessly keep your system operating at High Output levels*

**Value Engineered with:**

- ✓ Easy access slide-out airlock enables quick seal change.
- ✓ Intec's proprietary urethane casted seals last 2-3X longer than industry standard seals.
- ✓ Oversized positive displacement blower w/ splash lubrication provides quiet operation, low maintenance, with high airflow & associated production.
- ✓ Back-flow valve standard - provides for long lasting system by preventing material from backing up into blower.
- ✓ Pressure relief valve standard – ensures system does not create more pressure than desired to protect components.
- ✓ Air 'dump' valve standard – provides beneficial adjustments for sensitive wall assemblies.
- ✓ Fresh Air Inlets standard – provide clean air to Kohler and Blower motors enabling long life.
- ✓ Narrow width and low height enables operation from many vehicles in a variety of locations.
- ✓ Dual pulley's and belts with automatic tensioners drastically reduce maintenance.

integrity

excellence

innovation

trust

303-833-6644

[www.inteccorp.com](http://www.inteccorp.com)

Rev: 20230122

**Intec's Professional Grade Equipment**

Engineered for High Productivity


Built-to-Last for High Value Generation



Insulation Blowing Machines



## Specifications



- Weight: 1,015 lbs (461 kg)
- Hopper: 45 cubic feet
- Hose outlet: 3 inches (10.2cm)
- Motor: electric start Kohler V-Twin 19hp motor with 2 year / 2,000 hour Kohler warranty
- High volume positive displacement blower
- 40 chain with built-in tensioners & dual pulley's & belts for long lasting durability
- Fresh air intake for blower & Kohler motor
- 6 gallon removable gas tank
- Wired remote with 150' cord & Intec's exclusive urethane jacketed controls for long-life
- GOWIRELESS – optional Long Range Transmission High Performance wireless controls
- Warranty: 1 year limited

*Specs subject to change*


*note: Intec tests follow ASTM procedures. Hose length, diameter, product brand, humidity, and lift height will impact actual production.*

Product	Production (lbs per min)
Cellulose	35 – 40 <sup>+</sup>
Fiberglass	16 - 19

## Machine Features

### Shredding Chamber & Airlock


- ✓ Easy Access Gate with pin setting for quick material flow adjustments
- ✓ Easy Access Airlock with slide out feature – remove one chain and a few bolts for quick release
- ✓ Cast urethane seals for long-life



- Large 45 cu ft Hopper w/ generous loading platform
- ✓ 4-6 bags cellulose
  - ✓ 2-3 bags fiberglass




- ✓ Precision Feed Agitation



- ✓ 19h Kohler V-Twin Commercial Engine

Value Engineered Design for years of trouble-free operation:



- ✓ Backflow preventor
- ✓ Pressure relieve valve
- ✓ Gear box
- ✓ Dual pulleys & belts
- ✓ Automatic chain tensioners

## Additional Intec Systems & Accessories


### Heavy Duty Capabilities



### Intec's Popular Combatt Nozzles



### OptiSpray Nozzles



### Spray Tips & Filters




### Fluid Delivery Systems compact pumps



### Recycle Hood



Distributed by



Manufactured by

Insulation Technology Corporation, d.b.a. Intec  
9251 Bruin Boulevard  
Frederick, CO 80504



Local: 303-833-6644  
Fax: 303-833-6650  
sales@inteccorp.com

www.inteccorp.com

... it's the 'tec' inside that counts!