

GENERATOR

Intec Part #:
4000-16000

Generator 16kW

Generator

Professional Grade – 16,000 Watts ~ Meets Contractors' Demands



LED Display

Hours, RPMs, voltage, and frequency readings automatically cycle on the display.


Load Bars

Easily verify the load balance on each leg of the generator end.

Warnings

The LED will flash if any parameter gets outside of normal range. A warning will also be displayed when it is time for an oil change.

Receptacle Panel



Powered by HONDA iGX800 fuel injected V-Twin
Frequency regulation for sensitive electronics



integrity

excellence

innovation

trust

800-666-1611

www.inteccorp.com

Rev: 20240620



FORCE[®]

Insulation Blowing Machines



MEGA Beast Cyclone Fiber Force FORCE/2 HP FORCE/3 HP2 TURBO FORCE FORCE 5250 FORCE 5650 FORCE 5850

GENERATOR

Specifications

ENGINE

ENGINE BRAND	HONDA
ENGINE MODEL	IGX800
ENGINE STARTER	ELECTRIC
ENGINE SPEED	3600 RPM
ENGINE CYLINDERS	V-TWIN
DISPLACEMENT/TYPE	779 CC / OHV
FREQUENCY REGULATION ⁽¹⁾	+/- 3%
LOW OIL PROTECTION	STANDARD
RECOMMENDED OIL ⁽²⁾	5W-30
OIL CAPACITY	2.1 QT
FUEL TANK	15 GAL
FUEL GAUGE	YES
FULL LOAD RUN TIME ⁽³⁾	7 HOURS
FUEL CONSUMPTION	GAL/HR
100%	2.10
75%	1.71
50%	1.35
25%	0.96
0%	0.57

ELECTRICAL

STARTING WATTS	16,000
RUNNING WATTS	14,000
RUNNING AMPS @ 120 VAC	116
RUNNING AMPS @ 240 VAC	58
VOLTAGE REGULATION	CAPACITOR +/- 5%
MAIN CIRCUIT BREAKER	60 AMP, 240V VAC
BONDED NEUTRAL	YES
120 VOLT RECEPTACLES	(3) NEMA 5-20 20A DUPLEX (GFCI)
120/240 VOLT RECEPTACLES	(1) CSA369 SGA
240 VOLT RECEPTACLE	(2) NEMA L6-30 30A (GFCI)
YOURGEN METER	STANDARD

GENSET

MOTOR STARTING (CODE G)	4 HP
DBA @ 7 METERS	62
TOTAL HARMONIC DISTORTION	< 5%
LIFTING EYE ⁽¹⁾	STANDARD
4-WHEEL DOLLY KIT	OPTIONAL
INSULATION	CLASS H
PROTECTIVE ROLL FRAME	1.25" DIA. 14 GA. STEEL
ASSEMBLED IN	USA
EPA APPROVED	YES
CARB APPROVED	YES
TUV CERTIFICATION	CSA
UNIT WARRANTY ⁽²⁾	3 YEARS COMMERCIAL

NOTES: (1) Shipping eye shipped loose. (2) For more generator warranty, see operator's manual.

Features

HONDA iGX800 V-Twin Engine

- ✓ Fuel injected engine
 - ✓ Easier engine starting
 - ✓ Smoother, more consistent throttle response
 - ✓ Better fuel efficiency
 - ✓ Cleaner exhaust
 - ✓ Better frequency control – Self Tuning Regulator (STR) keeps you right at 60 hz from no load to full load

YourGen Meter

- ✓ LED meter displaying hours, RPMs, voltage, and frequency readings. Verifies the load balance with a load bar display. Warnings when a parameter is outside of normal range and when an oil change is needed.

Low Oil Protection

- ✓ In the event of low-oil level, the engine will shut down, which will protect the engine from damage.

Powder Coat Paint

- ✓ Incredibly strong finish.

Sturdy Wrap Around Cradle

- ✓ 13 Gauge, welded, tubular steel provides industrial strength support.

15 Gallon Fuel Tank

- ✓ EPA Approved steel fuel tank designed to eliminate hydrocarbon emissions.

Premium Circuit Breakers

- ✓ Provides a clear and instant indication of a tripped circuit.

Specifications subject to change; contact Intec for current specifications

Accessories



Wheel Kit Standard




Slide Out – options available
Part #: 77045-00 or 77046-00



Battery Standard

Distributed by



Manufactured by

Insulation Technology Corporation, d.b.a. Intec
9251 Bruin Boulevard
Frederick, CO 80504



phone: 303-833-6644

sales@inteccorp.com

www.inteccorp.com



... it's the 'tec' inside that counts!