



## Specifications



- Weight: 1,015 lbs (461 kg)
- Hopper: 45 cubic feet
- Hose outlet: 3 inches (10.2cm)
- Motor: electric start Kohler V-Twin 19hp motor with 2 year / 2,000 hour Kohler warranty
- High volume positive displacement blower
- 40 chain with built-in tensioners & dual pulley's & belts for long lasting durability
- Fresh air intake for blower & Kohler motor
- 6 gallon removable gas tank
- Wired remote with 150' cord & Intec's exclusive urethane jacketed controls for long-life
- GOWIRELESS – optional Long Range Transmission High Performance wireless controls
- Warranty: 1 year limited

*Specs subject to change*

*note: Intec tests follow ASTM procedures. Hose length, diameter, product brand, humidity, and lift height will impact actual production.*

Product	Production (lbs per min)
Cellulose	35 – 40+
Fiberglass	16 - 19

## Machine Features

### Shredding Chamber & Airlock

- ✓ Easy Access Gate with pin setting for quick material flow adjustments
- ✓ Easy Access Airlock with slide out feature – remove one chain and a few bolts for quick release
- ✓ Cast urethane seals for long-life




- Large 45 cu ft Hopper w/ generous loading platform
- ✓ 4-6 bags cellulose
  - ✓ 2-3 bags fiberglass


- ✓ Precision Feed Agitation



- ✓ 19h Kohler V-Twin Commercial Engine



Value Engineered Design for years of trouble-free operation:



- ✓ Backflow preventor
- ✓ Pressure relieve valve
- ✓ Gear box
- ✓ Dual pulleys & belts
- ✓ Automatic chain tensioners

## Additional Intec Systems & Accessories


### Heavy Duty Capabilities



### Intec's Popular Combatt Nozzles



### OptiSpray Nozzles



### Spray Tips & Filters




### Fluid Delivery Systems compact pumps



### Recycle Hood



Distributed by



Manufactured by

Insulation Technology Corporation, d.b.a. Intec  
9251 Bruin Boulevard  
Frederick, CO 80504



Local: 303-833-6644  
Fax: 303-833-6650  
sales@inteccorp.com

www.inteccorp.com

... it's the 'tec' inside that counts!